



EC BUDDY

Charge safely and efficiently

Charging a battery must be simple and safe. In order to deliver safe and effective charging, requires a charger of which high quality is the result of well-developed solutions.

Swede Electronics has since the start of its business in 1982 been known to develop well thought through solutions with focus on our customers' needs and requirements.

Over the years we have been at the forefront of technical advancement.

We believe that our high standards and our way of working is the reason to why we today are known as a company that offers the right product at the right time.



EC Buddy benefits include:

- » Ergonomic and modern design
- » Build-in data logger
- » Remote monitoring
- » Noiseless – no fan
- » Attention with sound
- » Temperature compensated charging
- » High efficiency

More than
battery charging!

EC Buddy is a fully automatic, primary switch battery charger with built-in data logger and remote monitoring. You can switch between two different charging current by default, and there is also a reprogramming option if other parameters are required to be changed. It can be advantageously supplied with an internal temperature sensor, which means that the charging program always charges the battery effectively without the risk of over or under charging.

The high security of the charger is achieved through advanced technology. Not least, the charging cables are voltage-free until the battery is securely connected, eliminating the risk of sparking during switching on.

EC Buddy can be set to store key data for the latest charging cycles on a central server. The information can be read out at any time via a computer, tablet or mobile phone with internet access and is used to optimize battery size and consumption pattern, as well as ensure warranty obligations and schedule service visits etc.

Thanks to a fully automatic charging process and precise control of power and voltage levels, we can guarantee that the batteries are charged efficiently with minimal gas and heat generation.

EC Buddy comes in a smart and modern design with an integrated handle and is made of a splash-proof plastic cabinet without fan, which makes it noiseless.

Technical data

Type	ECB-601	ECB-801	ECB-1001
Charging current	6 A	8 A	10 A
Charging voltage	24 V – 12 cells	24 V – 12 cells	24 V – 12 cells
Recommended capacity	AGM/Gel 18–60 Ah	AGM/Gel 25–80 Ah	AGM/Gel 33–100 Ah
Mains voltage	230 V (184–253 V AC)	230 V (184–253 V AC)	230 V (184–253 V AC)
Mains current	1.3 A @ 230 V	1.7 A @ 230 V	2.2 A @ 230 V
Charging characteristic	IUoU/IUIoU	IUoU/IUIoU	IUoU/IUIoU
Start-up voltage	17 V	17 V	17 V
Temperature compensated charging	Option –20°C–+50°C	Option –20°C–+50°C	Option –20°C–+50°C
Remote monitoring	Option	Option	Option
Temperature range	0°C–+40°C	0°C–+40°C	0°C–+40°C
Cable	1.6 m	1.6 m	1.6 m
Weight	1.3 kg	1.3 kg	1.4 kg
Cooling	Passive, no fan	Passive, no fan	Passive, no fan
Isolation class	II	II	II
Casing class	IP54	IP54	IP54
Dimensions (H x W x D) mm	205 x 179 x 90	205 x 179 x 90	205 x 179 x 90
Standard	EN 60335-2-29 EN 12184 ISO 7176-14 ISO 7176-21	EN 60335-2-29 EN 12184 ISO 7176-14 ISO 7176-21	EN 60335-2-29 EN 12184 ISO 7176-14 ISO 7176-21

Materials and specifications are subject to change without notice.



Head Quarter:
Swede Electronics AB
Fabriksvägen 8
SE-786 33 Vansbro, Sweden

Contact:
Phone: +46 281 304 00
Web: swedeelec.se
E-mail: info@swedeelec.se

Sales office Europe:
Swede Electronics A/S
Birkmosevej 13 B
DK-6950 Ringkøbing
Phone: +45 76 20 66 66